



1. ALL RESISTORS IN OHMS. ALL RESISTORS 0.5W UNLESS MARKED OTHERWISE.
2. ALL CAPACITORS IN MICROFARADS UNLESS OTHER PREFIX MARKED, THEN REPLACE PREFIX (MICRO) IN UNIT (MICROFARAD) WITH MARKED PREFIX. ALL CAPACITORS 25V (MINIMUM VOLTAGE RATING) UNLESS MARKED OTHERWISE.
3. ALL VOLTAGES IN VOLTS.
4. TRANSISTORS Q1, Q2: 2N5086.
5. TRANSISTORS Q3, Q4: MPSA18.
6. TRANSISTORS Q5, Q8: MPSA06.
7. TRANSISTOR Q6: MPSA56.
8. TRANSISTOR Q7: 2N5088.
9. TRANSISTOR Q9: MPSU06.
10. TRANSISTOR Q10: MPSU56.
11. TRANSISTOR Q11: TIF36C.
12. TRANSISTOR Q12: TIF35C.

13. IC Q13: 4N28.
14. DIODE D1: 1N4148.
15. DIODES D2, D3: 1N4002.
16. DIODES D4, D5, D6, D7: 1N5401.
17. ZENER DIODES D8, D9: 1N5244B.
18. PARTS NOT USED IN MODELS RG60 AND RB60: C13, C15.
19. LABEL(S) NOT USED: R32.
20. LAST REFERENCED DESIGNATION ON SCHEMATIC: R37, C15, D9, Q13, L1, P1, J1.

RIC Rickenbacker International Corp.
 3895 S. Main Street
 Santa Ana, Ca. 92707
 Tel: 714-545-5574 Fax: 714-754-0135

SCHEMATIC, POWER AMP RG90, RG60, RB60

SCALE	NA	CHECKED BY	DRAWN BY
DATE	3/1/89	J. HALL	K. MASCARENHAS
SIZE	DRAWING NO		19334
B			